

This information was generated by the HP KEYMARK database on 25 Feb 2023

	ecoGEO B1/C1 1-6 PRO	Reg. No.	011-1W0429
Certificate Holder			
	Ecoforest Geotermia S.L.		
	Rúa das Pontes, 25		36350
	Nigrán (Pontevedra)		Spain
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	ecoGEO B1/C1 1-6 PRO		
Heat Pump Type	Brine/Water		
Refrigerant	R290		
Mass of Refrigerant	0.15 kg		
Certification Date	17.11.2020		
Testing basis	HP KEYMARK certification scheme rules rev. 7		

Model: ecoGEO C1 1-6 PRO

Configure model	
Model name	ecoGEO C1 1-6 PRO
Application	Heating + DHW + low temp
Units	Indoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	2.58 kW	4.39 kW
El input	0.60 kW	1.53 kW
COP	4.30	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Warmer Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	134 %
Prated	6.00 kW	5.50 kW
SCOP	4.65	3.56
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	5.82 kW	5.50 kW
COP Tj = +2°C	3.72	2.79
Cdh Tj = +2 °C	0.990	0.990
Pdh Tj = +7°C	3.86 kW	3.55 kW
COP Tj = +7°C	4.43	3.27
Cdh Tj = +7 °C	0.990	0.990
Pdh Tj = 12°C	1.71 kW	3.44 kW
COP Tj = 12°C	5.37	4.24
Cdh Tj = +12 °C	0.960	0.990
Pdh Tj = Tbiv	5.82 kW	5.50 kW

This information was generated by the HP KEYMARK database on 25 Feb 2023

COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	1728 kWh	2066 kWh

Colder Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	186 %	141 %

This information was generated by the HP KEYMARK database on 25 Feb 2023

Prated	6.00 kW	5.50 kW
SCOP	4.85	3.73
Tbiv	-22 °C	-22 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	3.64 kW	3.35 kW
COP Tj = -7°C	4.59	3.42
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	2.24 kW	2.06 kW
COP Tj = +2°C	5.27	4.04
Cdh Tj = +2 °C	0.970	0.980
Pdh Tj = +7°C	1.44 kW	1.41 kW
COP Tj = +7°C	5.40	4.40
Cdh Tj = +7 °C	0.960	0.960
Pdh Tj = 12°C	0.88 kW	1.19 kW
COP Tj = 12°C	4.91	4.77
Cdh Tj = +12 °C	0.940	0.950
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		

This information was generated by the HP KEYMARK database on 25 Feb 2023

WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	3059 kWh	3631 kWh

Average Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	136 %
Prated	6.00 kW	5.50 kW
SCOP	4.64	3.60
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = -7°C	5.35 kW	4.45 kW
COP Tj = -7°C	3.87	2.89
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.28 kW	2.73 kW
COP Tj = +2°C	4.68	3.60
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.10 kW	2.01 kW
COP Tj = +7°C	5.26	4.14
Cdh Tj = +7 °C	0.970	0.980
Pdh Tj = 12°C	1.24 kW	1.16 kW
COP Tj = 12°C	5.44	4.48
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W

This information was generated by the HP KEYMARK database on 25 Feb 2023

PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Q _{he}	2669 kWh	3152 kWh

Domestic Hot Water (DHW)

Warmer Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Colder Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Average Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Model: ecoGEO C2 1-6 PRO

Configure model	
Model name	ecoGEO C2 1-6 PRO
Application	Heating + DHW + low temp
Units	Indoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz
Off-peak product	Yes

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	2.58 kW	4.39 kW
El input	0.60 kW	1.53 kW
COP	4.30	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Warmer Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	134 %
Prated	6.00 kW	5.50 kW
SCOP	4.65	3.56
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	5.82 kW	5.50 kW
COP Tj = +2°C	3.72	2.79
Cdh Tj = +2 °C	0.990	0.990
Pdh Tj = +7°C	3.86 kW	3.55 kW
COP Tj = +7°C	4.43	3.27
Cdh Tj = +7 °C	0.990	0.990
Pdh Tj = 12°C	1.71 kW	3.44 kW
COP Tj = 12°C	5.37	4.24
Cdh Tj = +12 °C	0.960	0.990
Pdh Tj = Tbiv	5.82 kW	5.50 kW

This information was generated by the HP KEYMARK database on 25 Feb 2023

COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	1728 kWh	2066 kWh

Colder Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	186 %	141 %

This information was generated by the HP KEYMARK database on 25 Feb 2023

Prated	6.00 kW	5.50 kW
SCOP	4.85	3.73
Tbiv	-22 °C	-22 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	3.64 kW	3.35 kW
COP Tj = -7°C	4.59	3.42
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	2.24 kW	2.06 kW
COP Tj = +2°C	5.27	4.04
Cdh Tj = +2 °C	0.970	0.980
Pdh Tj = +7°C	1.44 kW	1.41 kW
COP Tj = +7°C	5.40	4.40
Cdh Tj = +7 °C	0.960	0.960
Pdh Tj = 12°C	0.88 kW	1.19 kW
COP Tj = 12°C	4.91	4.77
Cdh Tj = +12 °C	0.940	0.950
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		

This information was generated by the HP KEYMARK database on 25 Feb 2023

WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	3059 kWh	3631 kWh

Average Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	136 %
Prated	6.00 kW	5.50 kW
SCOP	4.64	3.60
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = -7°C	5.35 kW	4.45 kW
COP Tj = -7°C	3.87	2.89
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.28 kW	2.73 kW
COP Tj = +2°C	4.68	3.60
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.10 kW	2.01 kW
COP Tj = +7°C	5.26	4.14
Cdh Tj = +7 °C	0.970	0.980
Pdh Tj = 12°C	1.24 kW	1.16 kW
COP Tj = 12°C	5.44	4.48
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W

This information was generated by the HP KEYMARK database on 25 Feb 2023

PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Q _{he}	2669 kWh	3152 kWh

Domestic Hot Water (DHW)

Warmer Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Colder Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Average Climate

EN 16147	
Declared load profile	L
Efficiency η_{DHW}	80 %
COP	1.82
Heating up time	1:50 h:min
Standby power input	100.0 W
Reference hot water temperature	57.0 °C
Mixed water at 40°C	220 l

Model: ecoGEO B1 1-6 PRO

Configure model	
Model name	ecoGEO B1 1-6 PRO
Application	Heating (medium temp)
Units	Indoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	2.58 kW	4.39 kW
El input	0.60 kW	1.53 kW
COP	4.30	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Warmer Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	134 %
Prated	6.00 kW	5.50 kW
SCOP	4.65	3.56
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	5.82 kW	5.50 kW
COP Tj = +2°C	3.72	2.79
Cdh Tj = +2 °C	0.990	0.990
Pdh Tj = +7°C	3.86 kW	3.55 kW
COP Tj = +7°C	4.43	3.27
Cdh Tj = +7 °C	0.990	0.990
Pdh Tj = 12°C	1.71 kW	3.44 kW
COP Tj = 12°C	5.37	4.24
Cdh Tj = +12 °C	0.960	0.990
Pdh Tj = Tbiv	5.82 kW	5.50 kW

This information was generated by the HP KEYMARK database on 25 Feb 2023

COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	1728 kWh	2066 kWh

Colder Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	186 %	141 %

This information was generated by the HP KEYMARK database on 25 Feb 2023

Prated	6.00 kW	5.50 kW
SCOP	4.85	3.73
Tbiv	-22 °C	-22 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	3.64 kW	3.35 kW
COP Tj = -7°C	4.59	3.42
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	2.24 kW	2.06 kW
COP Tj = +2°C	5.27	4.04
Cdh Tj = +2 °C	0.970	0.980
Pdh Tj = +7°C	1.44 kW	1.41 kW
COP Tj = +7°C	5.40	4.40
Cdh Tj = +7 °C	0.960	0.960
Pdh Tj = 12°C	0.88 kW	1.19 kW
COP Tj = 12°C	4.91	4.77
Cdh Tj = +12 °C	0.940	0.950
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		

This information was generated by the HP KEYMARK database on 25 Feb 2023

WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	3059 kWh	3631 kWh

Average Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	136 %
Prated	6.00 kW	5.50 kW
SCOP	4.64	3.60
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = -7°C	5.35 kW	4.45 kW
COP Tj = -7°C	3.87	2.89
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.28 kW	2.73 kW
COP Tj = +2°C	4.68	3.60
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.10 kW	2.01 kW
COP Tj = +7°C	5.26	4.14
Cdh Tj = +7 °C	0.970	0.980
Pdh Tj = 12°C	1.24 kW	1.16 kW
COP Tj = 12°C	5.44	4.48
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W

This information was generated by the HP KEYMARK database on 25 Feb 2023

PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Q _{he}	2669 kWh	3152 kWh

Model: ecoGEO B2 1-6 PRO

Configure model	
Model name	ecoGEO B2 1-6 PRO
Application	Heating (medium temp)
Units	Indoor
Climate Zone	Colder Climate + Warmer Climate
Reversibility	No
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	2.58 kW	4.39 kW
El input	0.60 kW	1.53 kW
COP	4.30	2.84

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Warmer Climate

This information was generated by the HP KEYMARK database on 25 Feb 2023

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	134 %
Prated	6.00 kW	5.50 kW
SCOP	4.65	3.56
Tbiv	2 °C	2 °C
TOL	2 °C	2 °C
Pdh Tj = +2°C	5.82 kW	5.50 kW
COP Tj = +2°C	3.72	2.79
Cdh Tj = +2 °C	0.990	0.990
Pdh Tj = +7°C	3.86 kW	3.55 kW
COP Tj = +7°C	4.43	3.27
Cdh Tj = +7 °C	0.990	0.990
Pdh Tj = 12°C	1.71 kW	3.44 kW
COP Tj = 12°C	5.37	4.24
Cdh Tj = +12 °C	0.960	0.990
Pdh Tj = Tbiv	5.82 kW	5.50 kW

This information was generated by the HP KEYMARK database on 25 Feb 2023

COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	1728 kWh	2066 kWh

Colder Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	186 %	141 %

This information was generated by the HP KEYMARK database on 25 Feb 2023

Prated	6.00 kW	5.50 kW
SCOP	4.85	3.73
Tbiv	-22 °C	-22 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	3.64 kW	3.35 kW
COP Tj = -7°C	4.59	3.42
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	2.24 kW	2.06 kW
COP Tj = +2°C	5.27	4.04
Cdh Tj = +2 °C	0.970	0.980
Pdh Tj = +7°C	1.44 kW	1.41 kW
COP Tj = +7°C	5.40	4.40
Cdh Tj = +7 °C	0.960	0.960
Pdh Tj = 12°C	0.88 kW	1.19 kW
COP Tj = 12°C	4.91	4.77
Cdh Tj = +12 °C	0.940	0.950
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		

This information was generated by the HP KEYMARK database on 25 Feb 2023

WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	3059 kWh	3631 kWh

Average Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	44 dB(A)	44 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	178 %	136 %
Prated	6.00 kW	5.50 kW
SCOP	4.64	3.60
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C

This information was generated by the HP KEYMARK database on 25 Feb 2023

Pdh Tj = -7°C	5.35 kW	4.45 kW
COP Tj = -7°C	3.87	2.89
Cdh Tj = -7 °C	0.990	0.990
Pdh Tj = +2°C	3.28 kW	2.73 kW
COP Tj = +2°C	4.68	3.60
Cdh Tj = +2 °C	0.980	0.980
Pdh Tj = +7°C	2.10 kW	2.01 kW
COP Tj = +7°C	5.26	4.14
Cdh Tj = +7 °C	0.970	0.980
Pdh Tj = 12°C	1.24 kW	1.16 kW
COP Tj = 12°C	5.44	4.48
Cdh Tj = +12 °C	0.950	0.960
Pdh Tj = Tbiv	5.82 kW	5.50 kW
COP Tj = Tbiv	3.72	2.79
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	5.82 kW	5.50 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.72	2.79
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh		
WTOL	70 °C	70 °C
Poff	11 W	11 W
PTO	11 W	11 W
PSB	11 W	11 W

This information was generated by the HP KEYMARK database on 25 Feb 2023

PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Q _{he}	2669 kWh	3152 kWh